

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247309
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	300/400/100
Nominal power [W]:	32	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP54
Luminous flux [lm]:	4300	Plug type:	UNI-SCHUKO
Energy efficiency class:	D	Socket type:	PL-FR
Electrical protection class:	I	Sockets:	2
Colour temperature [K]:	4000	Cable length [m]:	5
Beam angle [°]:	120	Net weight [kg]:	2.800
Diffuser material:	PC	Index:	247309
Diffuser type:	frozen	Category type:	workplace floodlights
Material of the body:	PP	ETIM class:	EC000347
Colour of the body:	grey	Manual:	Download PDF

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl